# 0150 - 21XX - 5.08mm - 상품코드 : 010101312



*착탈식 플러그(Plugs)타입 단자대입니다.
*착탈식 헤더타입과 연결하여 사용 가능한 제품입니다.
*PCB Connector Plug , Push in design
*0150 - 21XX, 5.08 mm, 300V, 16A

## 제품 상세 정보 (Product Features)

* 추가제품옵션탭 에서 Pole수 선택사용 가능합니다.
이 제품은 필요로 하는 어플리케이션에 맞추어 원하는 pole 수에 맞추어 주문 가능 한 품목입니다.

※ 유의사항
상기 제품에 첨부된 데이터시트는 참고용입니다.
자세한 데이터시트를 원하실 때에는 당사에 문의 바랍니다.

## 핵심 정보 (Key information)

| | |
|---|---|
| 허용전류 | 16A |
| 허용전압 | 300V |
| 생산가능핀수 | 2P~24P |
| 핀간격 | 5.08 mm |

## 기술데이터


| Technical Data | |
|---|---|
| Conductor cross - section, solid | 0.2~2.5 |
| Conductor cross - section, flexb | 0.25~1.5 |
| INSULATING MATERIAL | PA |
| UL UG Group | B, D |
| WIRE STRIP LENGTH | 11mm |



TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

Drawing




Dimension

| | |
|---|---|
| 카테고리 | PCB Connector - Plug |
| 핀간격 (mm) | 5.08 |
| 색상 | Black (default) |
| 커넥션방식 | Push-in Design |
| 락킹타입 | With lock flange |
| 길이 (mm) | 5.08*(P-1)+5.6 |
| 너비 (mm) | 24.4 |
| 높이 (mm) | 28.8 |
| 폴수(핀수) | 02P~24P |
| 단수 | Single level |

Specification



TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

## 원자재 정보

| | |
|---|---|
| 절연자재 | PA |
| 절연자재 그룹 | I |
| UL 94에 따른 난연등급 | V0 |
| 절연저항 | ≥500MΩ at DC 500V |
| 전도체 원자재 | COPPER ALLOY |
| 도체표면 도금처리 | Tin PLATED |

Material

## 커넥션 데이타-UL

| | |
|---|---|
| 정격전압(UL/CUL Group B) (V) | 300 |
| 정격전류(UL/CUL Group B) (A) | 16 |
| 정격전압(UL/CUL Group D) (V) | 300 |
| 정격전류(UL/CUL Group D) (A) | 10 |
| UL/CUL 규격에 따른 최소단선 AWG | 24 |
| UL/CUL 규격에 따른 최대단선 AWG | 12 |
| UL/CUL 규격에 따른 최소연선 AWG | 24 |
| UL/CUL 규격에 따른 최대연선 AWG | 12 |

Connection data (UL)



TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved