0156 - 29XXL - 3.5mm - 상품코드 : 010101196



*0156 S - Cage series
*3.5mm간격 초소형 2단 모델(최적의 공간 활용가능)
*0156 - 29XXL, 150V, 8A

제품 상세 정보 (Product Features)

*0156 시리즈는 스위치를 누를 필요없이 와이어를 바로 삽입하는 PUSH - IN 모델로써, 작업속도를 현저히 향상할 수 있습니다.

*특허설계인 딘클의 착탈방식은 고정형 추가 스크류 없이 진동 및 흔들림에 완벽한 구조를 갖고 있습니다.

*이 제품은 UL 및 VDE를 통하여 IEC60998 및 UL1059 승인에 맞도록 제조되었습니다.

※ 유의사항

상기 제품에 첨부된 데이터시트는 참고용입니다.
자세한 데이터시트를 원하실 때에는 당사에 문의 바랍니다.

핵심 정보 (Key information)

폴 넘버	06POLE
허용전압	150V
허용전류	8A
핀간격	3.50 mm
생산가능핀수	3PX2 ~ 20PX2


기술데이터

Technical Data	
Rated current	8A
Rated voltage	150V
Pitch	3.50mm


TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

Drawing



Dimension




阴影肋的数量表

P	6	8	10	12	14	16	18	20	22
肋数量	6-18P之间都有肋							7	8
P	24	26	28	30	32	34	36	38	40
肋数量	7	8	7	8	7	8	9	10	11

Dimension

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved



PCB Layout

ITEM	NAME OF PART	MATERIAL	NOTES
4	SOLDER PIN 3	COPPER ALLOY	Tin Plated
3	SOLDER PIN 2	COPPER ALLOY	Tin Plated
2	SOLDER PIN 1	COPPER ALLOY	Tin Plated
1	HOUSING	LCP	UL94-V0 BLACK

Material

Normal Geometric Tolerancing					
— //			⏥	⊥	
0 to 100	0.2			0 to 10	0.2
over 100 to 150	0.3		0.3	over 10	0.3
over 150	0.5				
Total Pitch Tolerances			Normal dimension Tolerances		
0<U<=30	±0.20		0~30		±0.25
30<U<=53	±0.25		over 30~53		±0.30
53<U<=70	±0.30		over 53~70		±0.35
70<U<=90	±0.35		over 70~90		±0.44
90<U<=115	±0.44		over 90~115		±0.55
115<U<=150	±0.55		over 115~150		±0.70

Tolerance

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved